

Celebrity® XL Deluxe

LUXURY PERFORMANCE & STYLE

CELEBRITY® XL DELUXE

The **Celebrity® XL Deluxe Scooter** combines an aggressive outdoor design with luxury features. This feature-rich scooter takes the Celebrity line to an even higher level of refinement in scooter design with our new independent console angle adjustment, deluxe high-back reclining captain's seat, full directional light package and one-handed tiller angle adjustment, making it the best outdoor scooter in its class.



Pride[®]
Mobility Products
Australia Pty. Ltd.
— LIVE YOUR BEST[™] —

(Tel) 03 8770 9600 • (Fax) 03 9703 2720 • www.pridemobility.com.au

Celebrity® XL Deluxe

Weight capacity:	159 kg (350 lbs.)
Maximum speed ² :	Variable up to 12 km/h (7.5 mph)
Ground clearance ³ :	10.79 cm (4.25")
Turning radius:	168.27 cm (66.25")
Overall length ³ :	130.17 cm (51.25")
Overall width ³ :	64.13 cm (25.25")
Wheels:	
Front:	10.16 cm x 33.02 cm (4" x 13") Pneumatic
Rear:	10.16 cm x 33.02 cm (4" x 13") Pneumatic
Anti-tips:	Rear
Suspension:	Front and rear
Transport weight ³	
Total w/o batteries:	90.71 kg (200 lbs.)
Heaviest piece when disassembled:	37.64 kg (83 lbs.) (front section)
Drivetrain:	Rear-wheel drive, sealed transaxle, 24 volt DC motor
Dual braking system:	Regenerative and electromechanical (electronic, regenerative disc brakes)
Power elevating seat:	N/A
Std. Seating:	CRS Deluxe
Battery charger:	Off-board, 5 amp
Per-charge range ² :	Up to 40.23 km (25 miles)
Battery requirements:	(2) 12V deep cycle (Gel cell type recommended)
Battery size & weight ¹ :	40 AH: 14.7 kg (32.5 lbs.) each

Colours:



Features

- Front frame mounted seat post for optimal stability
- Restyled lightweight front basket included
- Easily accessible securement points (for transport of an unoccupied scooter)
- High visibility reflectors
- Microprocessor-based controller for optimal power management
- Ultra-simple, auto-latching frame lockup for quick disassembly and assembly
- Standard angle-adjustable dual bulb lower headlight for optimal pathway illumination
- Independent angle-adjustable console
- One-handed operational squeeze lever and auto-locking mechanism for convenient tiller angle adjustment
- Full directional lighting package including front and rear turn signal indicators
- Two rearview mirrors standard

Options

- Accepts both 40 AH and 50 AH batteries for optimum charge

¹Battery weight may vary based on manufacturer

²Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).

³Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.